

369.00 EUR  
incl. 19% VAT, plus [shipping](#)



- MB Model: NP93B-2930 / PICO
- INTEL® Bay Trail-M N2930 Processor
- 2GB default (4GB option)
- 1 \* mSATA
- Application: Panel PC, Commerce, Banking, Digital Signage, Gaming, Medical, POS/KIOSK, Industrial Automation, I.O.T, AIO

|                     |                                                                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • Product Dimension | • 129 (W) * 78 (D) * 68 (H) mm                                                                                                                                        |
| • Product Model     | • JBC410P93(W)-2930-B                                                                                                                                                 |
| • MB Model & Size   | • JNP93B-2930 / PICO                                                                                                                                                  |
| • CPU               | • Intel® Bay Trail-M SoC Processor                                                                                                                                    |
| • Memory            | • 2G (on board)                                                                                                                                                       |
| • Storage Space     | • 1 * mSATA                                                                                                                                                           |
| • I/O Port          | • Power SW * 1 , Power LED * 1 (Blue)<br>• Giga LAN Port * 1<br>• WiFi Port * 2 (JBC410P93W-2930-B only)<br>• HDMI Port * 1<br>• USB3.0 * 1 , USB2.0 * 5<br>• COM * 2 |
| • Power Source      | • 2 PIN Terminal block con * 1 (DC-12V)                                                                                                                               |
| • Temperature       | • Operating within 0~60 centigrade<br>• Storage within -10-70 centigrade                                                                                              |
| • Certification     | • EMC : CE , FCC<br>• Safety : RoHS , Erp                                                                                                                             |
| • Application       | • Industrial Control System                                                                                                                                           |