

369.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake N3350/N4200 SoC Processor
- Support 1 \* DDR3L 1866MHz SO-DIMM up to 8GB
- 2 \* USB3.0 ,1 \* GbE LAN ,1 \* HDMI , 1 \* Micro SIM
- Support M.2 (M-key, SATA interface, 2242) storage
- M/B Form Factor : PICO SBC (100x72mm)
- DC-12V\_40W Adapter

|                 |                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model        | – JNP691-3350 / PICO SBC<br>– JNP691-4200 / PICO SBC                                                                                                                        |
| Part No         | – HBJC400P691-335B / HBJC400P691-420B (non-WIFI)<br>– HBJC400P691W-335B / HBJC400P691W-420B (WIFI)                                                                          |
| BIOS            | – AMI Flash ROM                                                                                                                                                             |
| CPU/Chipset     | – Intel® Apollo Lake N3350/N4200 SoC Processor                                                                                                                              |
| Memory          | – 1 * DDR3L-1866 SO-DIMM slots up to 8GB total                                                                                                                              |
| Storage         | – 1 * M.2 – 2242 (M-KEY)                                                                                                                                                    |
| Expansion Slot  | – 1 * Full-size mini-PCIE slot (for 802.11 b/g/n + BT 4.0 installed in WIFI model)                                                                                          |
| Network         | – 1 * Realtek RTL8111H GbE                                                                                                                                                  |
| Rear I/O Port   | – 2 * USB 3.0 ports<br>– 1 * HDMI (Max. resolution: 3840×2160@30Hz)<br>– 1 * RJ45<br>– 1 * SIM Card Holder<br>– 1 * Kensington lock<br>– 3 * Antenna holes<br>– 1 * DC Jack |
| Front Panel I/O | – 1 * Power button<br>– 1 * Power LED                                                                                                                                       |
| Power Source    | – AC-DC FSP Adapter / DC12V-3.3A-40W<br>– AC 90~240V input                                                                                                                  |
| Compliance      | – CE, FCC, RoHS, ErP Ready                                                                                                                                                  |
| Temperature     | – Operating Temperature : 0°C~50°C<br>– Storage Temperature : -20°C~70°C                                                                                                    |
| Dimensions      | – 129 (W) x 78.4 (D) x 34 (H) mm                                                                                                                                            |

|            |                                                                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packing    | <ul style="list-style-type: none"><li>– Net Weight: 0.8KG</li><li>– Gross Weight■1.5KG</li><li>– Color Box Dimension■156 (W) * 167 (D) * 123.6 (H) mm</li></ul> |
| OS Support | – Windows 10 , Linux                                                                                                                                            |
| Warranty   | – 2 Year limited warranty                                                                                                                                       |