



1039.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Whiskey Lake !
- Robust !
- DIN-Rail Mount !
- Fanless !

Support: [Datasheet](#)

The HM-5000S series Fanless system features the Intel Gen. 8th/10th Core i Processor power, with rich IO and excellent heat dissipation solution. HM-5000S series supports 12~36V power and Over-voltage & Over-current protection, and remote power switch by terminal block connection.

HM-5000S supports rich internal IO options: Dual Channel SODIMM, M.2 M Key with support NVMe SSD, M.2E Key for Wi-Fi6 Module installation, and M.2 B Key for 4G/5G module connection in a compact size.

- Intel Gen. 8th/10th Core i U-Series CPU
- 2* SO-DIMM DDR4 2400/2133 Dram (Max 64GB)
- 2* RS232/422/485, 6* GbE
- 16-bit GPIO
- Support 4G/5G (M.2 B Key + Nano SIM Holder) Module, Wi-Fi6 Module (M.2 E Key)

- 12~36V DC-in with OCP/OVP
- Remote Power Switch Design

Model	– HM-5002S (vPRO Model) – HM-5004S (Default) – HM-5007S (Essential Model)
General	
Certification	– FCC, CE, ROHS
Dimensions	– 216.8 x 124 x 86mm (W x D x H)
Mounting	– Wall Mount, Din Rail Mount
Power Requirements	– 12 ~ 36VDC
Power Consumption	– Change according to CPU
OS Support	– Windows 10/11, Linux
Hardware	
BIOS	– AMI 128Mbit Flash BIOS
CPU	– HM-5002S (8365Ue, vPRO Model): Intel® Whiskey Lake Mobile U i5-8365Ue – HM-5004S (8265U, Default): Intel® Whiskey Lake Mobile U i5-8265U – HM-5007S (4305Ue, Essential Model): Intel® Whiskey Lake Mobile U Celeron 4305Ue
Memory	– 2* SO-DIMM DDR4 2400/2133 Dram (Max 64GB)
Graphics	– Intel® UHD Graphics (by CPU)
Ethernet	– 1* Intel® i219LM GbE – 5* Intel® i211V GbE
Storage	– 1* 2.5" external cold-swap SATA3 bay – 1* M.2 M key (2242/2280 size, SATA or NVMe interface for SSD)
Expansion	– 1* M.2 E key (2230 size, CNVi interface for WIFI/BT) – 1* M.2 B key (3042/3052 size for 3G/4G/5G Module)
Front I/O Interface	
Serial Port	– 2* RS-232/422/485 with DB9 connectors, automatic RS-485 data flow control
Display	– 1* HDMI 1.4b, support 4096 x 2304@30Hz – 1* DP 1.2, support 4096 x 2304@60Hz
LAN	– 6* RJ45, 10/100/1000 Mbps
GPIO	– 16 bit GPIO (5V/12V)
USB	– 2* USB3.0 – 2* USB2.0
LED	– 1* Power LED – 1* HDD LED
Power Button	– 1* power button (Power LED)
Side I/O Interface	
Power Connector	– 1* 3 Pin, terminal Block with lock for Main board
Front Power Button	– 1* 2Pin for remote power switch function
Environment	
Temperature	– Operating■ -10 ~ 50°C – Storage■ -20 ~ 70°C
Relative Humidity	– 10 ~ 90% RH, non-condensing

CE/LVD/FCC Protection

- EN 55032 : 2015
- EN 55035 : 2017
- EN 61000-3-2 : 2019
- EN 61000-3-3 : 2013 + A1 : 2019
- EN 62368-1:2014 + A11 : 2017